

Specificaties Flexiheffer

capaciteit [kg]	25	50	100	150	200	250	760
radiusbereik [m]	3	3	3	3	3	3	2.5
	4	4	4	4	4	4	x
	4.5	4.5	4.5	4.5	4.5	x	x
	5	5	5	5	5	x	x
	5.5	5.5	5.5	5.5	x	x	x
	6	6	6	6	x	x	x
hefslag [m]	1.6	1.6	1.6	1.6	1.6	1.6	1.6
armhoogte [m]	2.7	2.7	2.8	2.8	2.8	2.8	2.8
hefslag [m]	2	2	2	2	2	2	2
armhoogte [m]	3.3	3.3	3.3	3.3	3.3	3.3	3.3
voeding [bar]	6	6	6	6	6	7	7
<i>uitvoeringen:</i>							
in wit/rood	ov	ov	ov	ov	ov	ov	b
in RVS 304	b	b	b	b	b	b	b
in RVS 316	b	b	b	b	b	b	b
in carbon	ov	b	b	x	x	x	x
in testcenter	ov	ov	ov	ov	ov	ov	x
in huurvloot	ov	ov	ov	ov	ov	ov	x
<i>optioneel:</i>							
mobiele voet	ov	ov	ov	ov	ov	ov	x
houdfuncties	ov	ov	ov	ov	ov	ov	ov