

**Specificaties Master Balancer**

categorie	I	I-b	II	II-b	IV	V
	1.75	2.2	5.25	6.5	8.5	
<b>r-bereik.[m]/cap.[kg]</b>						
<b>2.5</b>	70	90	210	260	340	900
<b>3</b>	60	75	175	215	285	x
<b>3.5</b>	50	65	150	185	245	x
<b>4</b>	45	55	130	165	215	x
<b>4.5</b>	40	50	120	145	190	x
<b>5</b>	35	45	105	130	170	x
<b>5.5</b>	30	40	95	120	155	x
<b>6</b>	30	35	85	110	140	x
<b>topsnelheid [m/min]</b>	50	50	50	50	25	25
<b>hefslag 1.75 [m]</b>	ov	b	ov	b	ov	ov
<b>hefslag &gt; 1.75 [m]</b>	b	b	b	b	b	b
<b>voeding [bar]</b>	6	7	6	7	7	7
<b>uitvoeringen:</b>						
<b>in wit/rood</b>	ov	b	ov	b	ov	ov
<b>in RVS 304</b>	b	b	b	b	b	b
<b>in RVS 316</b>	b	b	b	b	b	b
<b>in testcenter</b>	ov	x	ov	x	ov	x
<b>in huurvloot</b>	ov	x	ov	x	x	x
<b>optioneel:</b>						
<b>mobiele voet</b>	ov	ov	ov	ov	x	x
<b>houdfuncties</b>	ov	ov	ov	ov	ov	ov

ov = op voorraad c.q. direct leverbaar

b = beschikbaar met levertijd

x = niet leverbaar